

Erembodegem, November 2019

Dear Customer,

We would like to inform you about a technological improvement with the introduction of the new CA0 Cable Adaptors used in the Euromold 24kV connector kits.

The new cable adaptor CA0 (CA “zero”) will replace the 430CA and 411CA used in

- separable connectors types K480TB, K800PB
- separable connectors types K430TB, K300PB

This change will be implemented for all kits up to 12.7/22 (24) kV.

In a later stage, this change will also be implemented for

- the separable connectors types 400TB and 400LR
- M-level products (36 kV)



411CA

430CA

CA0

The new CA0 has following advantages:

- Easier to install
  - The elasticity has been improved, which makes it easier to install (less force needed)
- No need to put field control mastic
  - No field control mastic is needed on the semicon step, due to the increased elasticity
- All types of earthing connections are covered by a single cable adaptor
- Offers a watertight solution for outdoor use by means of the MWS (Mastic Water Sealing)
- Better eco footprint than the 430CA / 411CA (by removing all metal oxides from the compound)

Nexans Network Solutions N.V. - Div. Euromold – Zuid III – Industrielaan 12 – B-9320 Erembodegem  
Tel.: +32(0)53 85 02 11 – Fax: +32(0)53 83 10 13

- Qualified with type test according to CENELEC HD629.1
  - Test reports are available upon request

The complete kits will keep the current Item Number and Description, except for the 0 added in the description. The new CA0 will be included in the box as well as the modified installation instructions.

The new CA0 covers the complete range of both cable adapters 430CA and 411CA:

411CA	430CA	CA0	
<b>411CA-11</b> 12.0 mm - 17.5 mm	<b>430CA-11</b> 12.0 mm - 17.5 mm	<b>CA0-11</b> 12.0 mm - 19.0 mm	Diam. over insulation
<b>411CA-15</b> 16.0 mm - 22.0 mm	<b>430CA-16</b> 17.0 mm - 23.5 mm	<b>CA0-15</b> 16.0 mm - 26.5 mm	
<b>411CA-19</b> 20.0 mm - 26.5 mm	<b>430CA-18</b> 19.0 mm - 32.6 mm	<b>CA0-18</b> 19.0 mm - 32.6 mm	
<b>411CA-22</b> 23.5 mm - 31.0 mm	<b>430CA-22</b> 23.5 mm - 32.0 mm	<b>CA0-21</b> 22.0 mm - 34.6 mm	
<b>411CA-25</b> 26.5 mm - 32.5 mm			
<b>411CA-27</b> 28.5 mm - 37.5 mm	<b>430CA-27</b> 28.5 mm - 37.5 mm	<b>CA0-27</b> 28.5 mm - 37.5 mm	

We trust this change will improve the installer's experience as well as contribute to the continuous improvements of the Euromold connectors.

More information can be found on our website ([www.euromold.be](http://www.euromold.be)) or scan this code for more information:



Our entire Sales and Customer Service team remains at your service for any further information,

Sincerely yours,

Dusan Lazarevic  
Sales Director Western Countries

Rob Cardigan  
Segment Manager Connectivity

Nexans Network Solutions N.V. - Div. Euromold – Zuid III – Industrielaan 12 – B-9320 Erembodegem  
Tel.: +32(0)53 85 02 11 – Fax: +32(0)53 83 10 13