



Confirmation of Product Type Approval

Please refer to the "Service Restrictions" shown below to determine if Unit Certification is required for this product. This certificate reflects the information on the product in the ABS Records as of the date and time the certificate is printed.

Pursuant to the Rules of the American Bureau of Shipping (ABS), the manufacturer of the below listed product held a valid Manufacturing Assessment (MA) with expiration date of 08/SEP/2020. The continued validity of the Manufacturing Assessment is dependent on completion of satisfactory audits as required by the ABS Rules.

And; a Product Design Assessment (PDA) valid until 25/SEP/2021 subject to continued compliance with the Rules or standards used in the evaluation of the product.

The above entitle the product to be called Product Type Approved.

The Product Design Assessment is valid for products intended for use on ABS classed vessels, MODUs or facilities which are in existence or under contract for construction on the date of the ABS Rules used to evaluate the Product.

ABS makes no representations regarding Type Approval of the Product for use on vessels, MODUs or facilities built after the date of the ABS Rules used for this evaluation.

Due to wide variety of specifications used in the products ABS has evaluated for Type Approval, it is part of our contract that; whether the standard is an ABS Rule or a non-ABS Rule, the Client has full responsibility for continued compliance with the standard.

Product Name: Cable, Ship & Offshore Electrical Power
Model Name(s): MPRXCX, MPRXCX FLEXISHIP 1.8/3kV, MPRXCX EMC,
MPRXCX EMC FLEXISHIP 1.8/3kV

Presented to:

NEXANS DEUTSCHLAND GMBH
BONNENBROICHER STR. 2-14
Germany

Intended Service:

Ship and Offshore Electrical Power Cables Not intended for use as propulsion cable.

Description:

Conductor Material: stranded CL2 or CL5, red or tinned copper; Cross-sections: 1 core 25 to 300mm², 3 cores 25 to 150mm²; Insulation Material: XLPE; Inner Covering: halogen free material, Extruded or lapped; Armouring: copper braid and/or copper polyester tape; Outer Sheath Material: SHF1; SHF1 with enhanced resistance to scratching and optional SHF2; Flame retardant. Low smoke. Halogen free.

Ratings:

Maximum Conductor Temperature: 90° C; Ampacity as per ABS Steel Vessel Rules 4-8-3/Table 6.

Service Restrictions:

Unit Certification is not required for this product. If the manufacturer or purchaser request an ABS Certificate for compliance with a specification or standard, the specification or standard, including inspection standards and tolerances, must be clearly defined.

Comments:

The Manufacturer has provided a declaration about the control of, or the lack of Asbestos in this product. Cables shall be provided with a continuous indication of cable marking in accordance with IEC Publication 60092-353.

Notes / Documentation:

Drawing No. EMC_18-3kV_V10, Data Sheet, EMC Version, Revision: -, Pages: 1
Drawing No. MG-S-025_MPRXCX_3kV, Data Sheet, Revision: -, Pages: 1 Drawing

No. TMP-SRV-2016-92-01, Test Report, 07.07.2016, Revision: -, Pages: 1

Term of Validity:

This Product Design Assessment (PDA) Certificate 16-HG1565890-PDA, dated 26/Sep/2016 remains valid until 25/Sep/2021 or until the Rules or specifications used in the assessment are revised (whichever occurs first). This PDA is intended for a product to be installed on an ABS classed vessel, MODU or facility which is in existence or under contract for construction on the date of the ABS Rules or specifications used to evaluate the Product. Use of the Product on an ABS classed vessel, MODU or facility which is contracted after the validity date of the ABS Rules and specifications used to evaluate the Product, will require re-evaluation of the PDA. Use of the Product for non ABS classed vessels, MODUs or facilities is to be to an agreement between the manufacturer and intended client.

ABS Rules:

2016 Steel Vessel Rules 1-1-4/7.7, 1-1-Appendix 3 and 4, 4-8-3/9 2016 Mobile Offshore Drilling Unit Rules 1-1-4/9.7, 1-1-Appendix 2 and 3, 4-3-4/7

National Standards:

International Standards:

IEC 60092-353, IEC 60228, IEC 60092-351, IEC 60092-359, IEC 60332-1, IEC 60332-3-22, IEC 61034/1 & 2, IEC 60754/1 & 2

Government Authority:

EUMED:

Others:

Model Certificate	Model Certificate No	Issue Date	Expiry Date
PDA	16-HG1565890-PDA	26/SEP/2016	25/SEP/2021



ABS Programs

ABS has used due diligence in the preparation of this certificate and it represents the information on the product in the ABS Records as of the date and time the certificate was printed. Type Approval requires Drawing Assessment, Prototype Testing and assessment of the manufacturer's quality assurance and quality control arrangements. Limited circumstances may allow only Prototype Testing to satisfy Type Approval. The approvals of Drawings and Products remain valid as long as the ABS Rule, to which they were assessed, remains valid. ABS cautions manufacturers to review and maintain compliance with all other specifications to which the product may have been assessed. Further, unless it is specifically indicated in the description of the product; Type Approval does not necessarily waive witnessed inspection or survey procedures (where otherwise required) for products to be used in a vessel, MODU or facility intended to be ABS classed or that is presently in class with ABS. Questions regarding the validity of ABS Rules or the need for supplemental testing or inspection of such products should, in all cases, be addressed to ABS.